



BODY GLOVE
WATER FILTER SYSTEMS
FILTERED. CLEANER. BETTER.

by **Water Inc.**

MODEL

DESCRIPTION

BG-6000
FULL FLOW
Water Filtration
System

Part # WI-BG6000FF

Shipping Wt: 6 lbs.



Part # WI-BG6000FF-KIT

Shipping Wt: 1 lbs.

Adapter kit to allow additional installation to EverHot, EverCold, ice maker and refrigerator accessories.

FULL FLOW Body Glove Water Filter System: HIGH FLOW RATE & ADVANCED FILTRATION.

Don't want to drill a second hole for a second filter faucet? No problem.

For installation with full-flow faucets such as your main kitchen faucet, pot fillers, prep sinks, master bath, home spa, children or guest bath. Also great for bar sinks and ice makers.

Get an adapter kit and plumb it to your refrigerator's dispenser.

NO DRILLING REQUIRED! INSTALLATION IS EASY.

Featuring **Quad-Stage filtration** and a ****0.2 Micron Pharmaceutical-Grade Membrane**. Includes a recyclable cartridge with an easy recycle program, and a filter change indicator.

FLOW RATE: 2.5 GPM

CAPACITY: 6,000 gallons or 1 year

Dimensions: W = 4.5" / D = 4.75" / H = 18.75"

(height includes 2.5" clearance for cartridge change purposes)

UTILIZES EXISTING FAUCET
high flow rate and large capacity

REDUCES: Chlorine Taste & Odor • **Cloudiness, Sediment, Rust
Giardia Lambliia Cysts • Cryptosporidium Parvum Cysts • *Molds and Algae***
*Lime Scale • **Oxidized Iron • **Oxidized Manganese • **Oxidized Sulfides
0.5 Micron Particulate Reduction - Class 1 • Lead

SELECTED VOLITILE ORGANIC CHEMICALS (VOCs):
Benzene, P-Dichlorobenzene, Toxaphene

**Based on Manufacturer's Data *Contains KDF, a bacteriostatic and lime-scale control agent
***Inhibits the sustained growth of Molds and Algae



System Tested and Certified by NSF International against NSF/ANSI Standards 42 and 53 in Model BG-6000 for the reduction of:

Standard 42 - Aesthetic Effects

- Chemical Reduction
- Chlorine Taste & Odor
- Mechanical Filtration
- Particulate Reduction- Class I

Standard 53 - Health Effects

- Chemical Reduction
- Lead • Benzene • P-Dichlorobenzene
- Toxaphene
- Mechanical Filtration
- Cysts



System shown here with 1/2" IPS stainless steel braided hoses (included) and the optional adapter kit.

BG-6000FFC
Replacement
Cartridge

Part # WI-BG6000FFC

Shipping Wt: 4 lbs.



FLOW RATE: 2.5 GPM / CAPACITY: 6,000 gallons or 1 year

EASY QUICK-CHANGE REPLACEMENT CARTRIDGE: Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze.

Includes a filter change indicator.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.



CA LISTED

MEETS CA PROP 65 STANDARDS



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.

ORDER DESK TEL: 800-322-WATER (9283) • EXT. 118 • FAX: 888-928-3746
eorders@waterinc.com WI/PPD CONFIDENTIAL waterinc.com