

## MODEL

## DESCRIPTION

### HousePure® Soft Whole House Water Softener

Part # WI-HP-SOFT-2

Shipping Wt: 185 lbs.



The HousePure high flow industrial water softener provides whole-house protection against costly water hardness scaling and lime scale build-up. Enjoy the gentle caress of softened water from every faucet, bath and shower. Extend the life of your home: softened water protects appliances, fixtures and plumbing lines. The HousePure Soft is an ideal solution for hard water spotting and scaling damage.

Features high flow 1-1/4" to 1-1/2" inlet/outlet connections and a 1/2" discharge outlet. An electronic water meter provides quick setup and programming, while an integrated battery backup offers peace-of-mind during power interruptions. The softener regenerates and self cleans on a regular basis using 100 gallons of water per regeneration cycle. Ideal for indoor and outdoor installations. (See acceptable temperature range specifications shown below.)

#### Includes Installation Parts and Install/Owner's Manual

**Flow Rate:** 19 GPM

**Dimensions (Including Salt Tank):** Width: 32" Height: 63" Depth: 22"

**Filter Capacity:** 48,000 grains of hardness

**Media Volume:** 2 cubic feet of high capacity cation resin

**Salt Tank Size:** 400 lbs. (Can be used with either potassium or sodium salt types.)

**Operating Temperature Range:** 34°F to 110°F (not appropriate for freezing temperatures)

**Water Pressure Range:** 20 PSI to 75 PSI

**Water Quality:** Not for use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

**Operating Voltage:** 24 VAC, 50/60 Hz, 120 VAC transformer included



Component Tested to NSF/ANSI Standard 42  
for material requirements.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.

### ADD OUR EXCLUSIVE **BONUSGUARD** TO THIS PRODUCT

The **BonusGuard** uses KDF® 55 to remove or reduce chlorine, control scale, bacteria, algae and water soluble heavy metals. Product flow rate is limited to 11gpm.

#### Upgrade to the Bonus Guard: **WI-HP-SOFT-2-BG**

*The installation of a reverse osmosis drinking water system is recommended for persons with heart disease, hypertension, high blood pressure or a low sodium diet.*



**MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)