



MODEL DESCRIPTION

HousePure® Secure Tankless Water Heater Protection Part # WI-HP-SECURE-1.50L (water entry left side)
 Part # WI-HP-SECURE-1.50R (water entry right side)
 Utilizing Siliphos Polyphosphate
 Recommended for all Tankless Water Heater Manufacturers



LEVEL 2 High Flow Tankless Water Heater Scale Prevention.

Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A dual-gradient 50 over 5 micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The gradient density filter design provides up to three times the dirt-holding capacity of similar size sediment cartridges. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations (not for below freezing temperatures). Features a 1-1/2" NPT inlet/outlet with a pressure-change gauge for peace-of-mind.

Includes powder-coated mounting bracket, flow indicator gauge, & filter-change spanner wrench

Max Flow Rate: 20 GPM

Dimensions: Width: 7.5" Height: 29" Depth: 8.75"

Filter Capacity: One year or when flow gauge indicates change needed

Incoming Water Temperature Range: 40°F to 100°F

Tools Required: Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings, and inlet gate valve



YOU CHOOSE!
RIGHT or LEFT
 water entry side

Water, Inc filter change indicator included

YOU CHOOSE!
RIGHT or LEFT
 water entry side

HousePure® Secure Replacement Cartridge Part # WI-HP-SECURE-1.50C



The HousePure Secure cartridge should be changed annually or when flow gauge indicates a change is needed sooner.

Utilizing Siliphos Polyphosphate

Capacity: One year or when gauge indicates change needed

Dimensions: Height: 20" Diameter: 4.5"

Included: replacement lubricated o-ring & filter change indicator.

Replacement Cartridge for HousePure® Secure 1.5" tankless water heater filter system. The dual-gradient 50 over 5 micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

Recommended for all Tankless Water Heater Manufacturers



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)