



MODEL DESCRIPTION

**HousePure® Secure Tankless Water Heater Protection** Part # WI-HP-SECURE-.75L (water entry left side)  
Part # WI-HP-SECURE-.75R (water entry right side)  
Utilizing Siliphos Polyphosphate  
Recommended for all Tankless Water Heater Manufacturers



**LEVEL 1 Tankless Water Heater Scale Prevention.**

Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A 5-micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations (not for below freezing temperatures). Features a 3/4" NPT inlet/outlet with a differential filter-change gauge for peace-of-mind.

**Includes mounting bracket, filter-change flow indicator gauge & filter-change spanner wrench**

**Max Flow Rate:** 9 GPM

**Dimensions:** Width: 5.25" Height: 25.75" Depth: 5.5"

**Filter Capacity:** One year or when flow gauge or timer indicates change needed

**Incoming Water Temperature Range:** 40°F to 100°F

**Tools Required:** Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings and inlet gate valve



**YOU CHOOSE!  
RIGHT or LEFT  
water entry side**

**Water, Inc filter change indicator included**

**YOU CHOOSE!  
RIGHT or LEFT  
water entry side**

**HousePure® Secure Replacement Cartridge** Part # WI-HP-SECURE-.75C



**The HousePure Secure cartridge should be changed annually or when flow gauge indicates a change is needed sooner.**

Utilizing Siliphos Polyphosphate

**Capacity:** One year or when gauge indicates change needed

**Dimensions:** Height: 20" Diameter: 2.5"

**Included: replacement lubricated o-ring & filter change indicator.**

Replacement Cartridge for HousePure® Secure 3/4" tankless water heater filter system. The 5-micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

Recommended for all Tankless Water Heater Manufacturers



**MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)