

HOUSEPURE® WHOLE HOUSE FILTER



Model 02

COMMERCIAL QUALITY WHOLE HOME WATER FILTER SYSTEM

Utilizes innovative, **salt and chemical-free technology** to extend the life of plumbing fixtures and appliances while providing great tasting and gentle water at every point of use in the home. These self-standing units are equipped with self-clean automatic backwashing. Two models are available, read below to see which model is right for your home.

CUSTOMERS CONCERNED WITH CHLORAMINES CAN UPGRADE THIS PRODUCT.

Our non-chemically impregnated coconut based activated carbon has been surface modified during manufacture. *Our product is 3 times more effective than competitive products and 15 times more effective than our standard HousePure media.*

Upgrade to more complete chloramine removal! Add -CHL to the part number below



Model 04



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.

HousePure® Whole House Water Filter System

Model 02

HousePure® Whole House Water Filter System

Model 04

Part# WI-HOUSEPURE-02

Part# WI-HOUSEPURE-04

WITH CHLORAMINE UPGRADE

WITH CHLORAMINE UPGRADE

Part# WI-HOUSEPURE-02-CHL

Part# WI-HOUSEPURE-04-CHL

Shipping Wt: 150 lbs.

Shipping Wt: 180 lbs.

Dimensions

Height: 64"
Width: 10"
Depth: with bypass connected 14" (straight out) / 13" (90° up)
Rough In Dimension: 57"

Dimensions

Height: 65"
Width: 12"
Depth: with bypass connected 18" (straight out, 90° up or down)
Rough In Dimension: 55"

Recommended for homes up to 4,000 square feet.

Recommended for homes 4,000 square feet and larger.

VALVE FLOW RATE: 21 GPM

VALVE FLOW RATE: 35 GPM

EFFECTIVE SYSTEM FLOW RATE: 12 GPM

EFFECTIVE SYSTEM FLOW RATE: 19 GPM

CONNECTION: 1" NPT

CONNECTION: 1 1/4" NPT

Optional sweat yokes up to 1 1/4" at additional cost*
1/2" discharge connection

Optional sweat yokes up to 1 1/2" at additional cost*
1/2" discharge connection

VALVE: Standard home or light commercial application

VALVE: Heavy-duty industrial

MEDIA: 1.5 cubic feet, GAC (Granular Activated Carbon)
4.5 lbs, KDF-55

MEDIA: 2 cubic feet, GAC (Granular Activated Carbon)
4.5 lbs, KDF-55

CHL UPGRADE MEDIA: 1.5 cubic ft, surface modified GAC
4.5 lbs, KDF-55

CHL UPGRADE MEDIA: 2 cubic ft, surface modified GAC
4.5 lbs, KDF-55

* Optional installation connections are available

* Optional installation connections are available



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)