



MODEL

DESCRIPTION

BG-3000
Water Filtration
System

Part # WI-BG3000



LEVEL 2 Body Glove Water Filter System.

Featuring Tri Stage filtration and advanced protection from particles 0.5 micron in size and larger. Includes a recyclable cartridge with an easy recycle program, and a filter change indicator.

FLOW RATE: 0.75 GPM
CAPACITY: 450 gallons or 1 year

Dimensions: W = 4.5" / D = 4.75" / H = 15.75"
(height includes 2.5" clearance for cartridge change purposes)



For filter faucet options, see our faucet guides: pages 52 & 53.
Enhance your water with an EverHot® Instant Hot System or EverCold® Water Chiller.

REDUCES: Chlorine Taste & Odor • Chloramines • **Cloudiness, Sediment, Rust
Giardia Lamblia Cysts • Cryptosporidium Parvum Cysts • *Lime Scale
Asbestos Fibers • **Oxidized Iron • **Oxidized Manganese • **Oxidized Sulfides
Lead • 0.5-1.0 Micron, Nominal Particulate Reduction, Class 1
Trihalomethanes (TTHMs) • Volatile Organic Chemicals (VOCs)

**Based on Manufacturer's Data *Contains KDF, a lime-scale control agent



System Tested and Certified by NSF International against NSF/ANSI Standards 42, 53 and CSA B48 3.1 in Model BG-3000 for the reduction of:

Standard 42 - Aesthetic Effects

- Chemical Reduction
- Chlorine Taste & Odor
- Chloramines
- Mechanical Filtration
- Particulate Reduction- Class I

Standard 53 - Health Effects

- Chemical Reduction
- Lead • TTHM • VOC
- Mechanical Filtration
- Cysts • Asbestos

BG-3000C
Replacement
Cartridge

Part # WI-BG3000C



FLOW RATE: 0.75 GPM / **CAPACITY:** 450 gallons or 1 year

EASY QUICK-CHANGE REPLACEMENT CARTRIDGE: Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze. Includes a filter change indicator.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.